

## PRIMER-RR

### Multi-purpose Primer

#### DESCRIPTION

Multi-purpose, ready-to-use primer for internal and external walls.

#### APPLICATIONS

- Primer for Microtopping
- Excellent adhesion on plaster, concrete, brick, marble, ceramic, cement based and gypsum based plaster.

#### SURFACE PREPARATION- APPLICATION

Substrates must be clean, dry, well-cured and free from oil, grease, cement laitance and loose parts. There is no need to wet the surface before applying PRIMER-RR.

Stir before use. It is possible to dilute the product with 10-20% clean water.

Consumption 3-400 g/sqm

PRIMER-RR may be applied to the substrate with either a roller or by brush or roller. The minimum waiting time is 2 hours.

#### TECHNICAL SPECIFICATIONS

SPECIFIC WEIGHT	1.56 Kg/Lt
TOXICITY	Non Toxic
LOWEST APPLICATION TEMPERATURE	10°C
STORAGE TEMPERATURE	Between + 5°C and + 35°C

#### PACKAGING

22.5 kg pails. Shelf-life 12 months.

#### NOTICE

In case of application on old surfaces, it is recommended to carry out some adhesion tests.

**IMPORTANT:**

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed anytime. Ideal Work products are for professional use and the company organizes periodical training of its customers on demand. Anyone who uses these products without qualification, takes all the risks connected. EDIT 01 dated 01/09/2016